# GIMBAL TRACK SPOT111

The multitalented gimbal for row lighting systems. Like its mounting pendants, the spotlight relies on the intense-beam AR111 E-CORE illuminants and its gimbal mounting ensures limitless freedom in use. The harmonious union of the light and illuminant are convincing thanks to their masterful radiation and they guarantee excellent structural integration.

**FEATURES**

- Replaceable bulb: Yes / AR111
- Dimmable: No
- Protection rating: IP 20
- Temperature range: 5 °C – 35 °C

**LIGHT DISTRIBUTION**




(cd/klm)

**DIMENSIONS**




(mm)

**DIMENSIONS**




(mm)

| COMPLETE SYSTEM | FINISH | COLOUR TEMPERATURE | LUMINOUS FLUX | BEAM ANGLE | LUMINOUS INTENSITY | WATTAGE | VOLTAGE 50/60 Hz | Ra (min) | LIFESPAN (L70) | BASE |
|---|---|---|---|---|---|---|---|---|---|---|
| **WARM WHITE** | | | | | | | | | | |
| LEDEUS00001S30 | White | 3000 K | 800 lm | 24° | 3,850 cd | 15 W | 230 - 240 V | > 80 | 25,000 h | G53 |
| LEDEUS00002S30 | Silver | | 800 lm | 24° | 3,850 cd | 15 W | 230 - 240 V | > 80 | 25,000 h | G53 |
| LEDEUS00003S30 | Black | | 800 lm | 24° | 3,850 cd | 15 W | 230 - 240 V | > 80 | 25,000 h | G53 |

| | FINISH | RATED VOLTAGE | FREQUENCY | BASE |
|---|---|---|---|---|
| **FIXTURE** | | | | |
| LEDEUS00001C | White | 230 - 240 V | 50/60 Hz | G53 |
| LEDEUS00002C | Silver | | | |
| LEDEUS00003C | Black | | | |

AR111 lamp to be ordered separately - see page 26